



Intelligent Control Console: GreCon Mission Control

Helping address your industrial fire protection challenges

YOUR BENEFITS

- ✓ **Maximum availability:** Maintenance and updates are carried out step by step and at the click of a button – with no system downtime. GreCon can analyse errors remotely, often eliminating the need for on-site technician visits.
- ✓ **Quick commissioning:** Pre-wiring by the customer saves time and manpower. Components are plug-ready, and the I/O check ensures plug & play functionality.
- ✓ **Efficient fault diagnosis:** The intuitive user interface with remote access and error search mode enables fast, pinpoint analysis – often without the need for on-site intervention.

INTELLIGENT CONTROL CONSOLE

The new generation GreCon Mission Control is more than a modern, user-friendly control unit – it is the heart of smart industrial fire protection strategies. As the central control console, GreCon Mission Control takes industrial fire protection to a new level: It collects, analyses, and visualises safety-relevant data, controls the GreCon system architecture, and enables the coordination of predictive maintenance.

Mission Control takes over the overarching control logic, enabling a decentralised architecture with other components like the GreCon Ranger. At the same time, Mission Control remains backwards compatible with even earlier generations of control units, remaining supported, ensuring solutions that grow with your needs.

| TECHNICAL DATA | MISSION CONTROL |
|--|-------------------------|
| Dimensions in mm (H x W x D) | 340 x 440 x 290 |
| Maximum power consumption | 500 W |
| Battery | 18 Ah / 12 V |
| Battery fuse | ATO 15 A (blue) |
| Power supply output fuse | ATO 30 A (green) |
| Power supply input fuse | C 6 A |
| Emergency power backup time | min. 4 h |
| Operating voltage | 110 / 230 V AC |
| Frequency range | 47 to 63 Hz |
| Conductor cross-section | max. 16 mm ² |
| Protection class | IP 55 |
| Ambient temperature | -5 to +50 °C |
| Relative humidity | min. 10 %, max. 90 % |
| Installation location | dry, vibration-free |
| Altitude | up to 2000 m |
| Pollution degree according to EN 61010-1 | 2 |
| Weight | approx. 30 kg |



Our experts are happy to advise you!

sales@fagus-grecon.com

Fagus GreCon

Fagus-GreCon Greten GmbH & Co. KG
Hannoversche Straße 58
31061 Alfeld · Germany

+49 5181-790
info@fagus-grecon.com
www.fagus-grecon.com

SCAN HERE
TO DISCOVER
MORE!

